



# Touchstone® DOCSIS® 3.0 Residential Gateway

**TG862A/S**  
**802.11n, 4 Port Router,  
and 2 Voice Lines**

## Configuration

- Compact non-Battery Model
- 8x4 Channel Bonding
- Multi Processor Technology for Highest Performance
- DOCSIS® 3.0 and PacketCable™ 1.1/1.5 compliant design
- EuroDOCSIS® and Dual Mode Scanning support on the TG862S
- Upgradable to PacketCable 2.0
- 4 port Gigabit Ethernet Wireless Router
- Integrated 2.4GHz 802.11n radio
- USB 2.0 Host Port
- Enhanced WebGUI Interface with Technician Level Access
- Supports Firewall, Parental Control, L2TP, RIP, DHCP and more
- Up to two lines of carrier-grade VoIP
- Multiple Protocol Support: PacketCable (NCS) and Session Initiation Protocol (SIP)
- Internal Power Supply for Highest Reliability



## Advanced Residential Gateway Solution for Voice, Data , and Wireless

The Touchstone® DOCSIS® 3.0 Residential Gateway is an 8x4 advanced gateway product. The TG862 combines two analog voice lines, a 4-port Gigabit Router, and a 802.11n wireless access point into a single device capable of supporting both home and small office applications. Using multi-processor technology, the TG862 can achieve high bandwidth performance without affecting voice quality, a historical ARRIS product standard. This feature packed unit will lead the future for advanced home and small office services.

## Enhanced Performance

Operators strive to push the limits on DOCSIS 3.0 performance delivered to the customer with both the Ethernet and the wireless interfaces. The 802.11n wireless interface can deliver the performance desired while also offering improvements in home coverage above those of previous technologies.

## Efficient and Flexible Maintenance

The TG862 distinguishes itself with capabilities that minimize an operator's support needs. Multiple provisioning methods (SNMP, Configuration File, Remote WebGUI access, TR-069, and TFTP) allow a custom designed setup to be efficiently applied to the end user. Multiple local and remote access levels (User , Technician) also allow more ease and flexibility for manual configuration and control.

**TANTEC**  
*Digital*

TANTEC Digital AS  
www.tantec.no  
Tlf: +47 64838100

# Touchstone® DOCSIS® 3.0 Residential Gateway With 802.11n, 4 Port Router, and 2 Voice Lines

- DOCSIS® 3.0 and EuroDOCSIS™ compliant designs
- Dual Mode Scanning Support for the TG862S Model
- Up to 8 downstream channels supporting over 320Mbps of data capacity
- Up to 4 upstream channels supporting over 120Mbps of data capacity
- Tuners support two 96MHz blocks for up to 8 bonded channels
- High performance Wi-Fi® Alliance certified 802.11b/g/n wireless access point
- Advanced MIMO antenna configuration for optimal throughput and coverage
- High Speed Internet via 4 ports 10/100/1000Base-T Ethernet (RJ-45)
- All ports support Auto-negotiation, auto speed sensing, and Auto MDIX
- Multiple (4) SSID Support. Expandable to 8 SSIDs.
- WPA™ and WPA2™ Personal and Enterprise, 64 / 128 bit WEP, and MAC authentication wireless security options
- Support for WMM® QOS and WMM Power Save
- Wi-Fi Protected Setup™ (facilitates easy set-up of security using a Personal Identification Number (PIN) and/or a button located on the Wi-Fi device )
- Software support for UPnP
- USB 2.0 powered Host Port
- Support for Static and Dynamic IP, DHCP, NAT, L2TP, VLANs, and RIPv2
- Dual Color LED Status Information for defining operational status
- Low Power Consumption
- Integrated Universal Power Supply for Higher Reliability
- Power Switch on “S” Model
- Vertical or Horizontal Mounting
- 2 lines of Carrier Grade Voice
- Multiple Protocol Support: PacketCable (NCS) and Session Initiation Protocol (SIP)
- Toll grade, compression, and High Fidelity Wideband CODECs (HD) supported.
- Linux operating system allows for futures potential upgrades such as DLNA, and File Sharing Support.



**TANTEC**  
Digital

TANTEC Digital AS  
www.tantec.no  
TIP: +47 64639100

©ARRIS Enterprises, Inc. 2013 All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, Inc. ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS and the ARRIS logo are all trademarks of ARRIS Enterprises, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice.

**ARRIS**

www.arrisi.com