



Heating thermostat HT2

Radiator thermostat for controlling the temperature of radiators in hot water heating systems

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588095199	white	0000/9519	254 g	156 g	8.50 x 7.00 x 5.50 cm	10.00 x 14.00 x 6.00 cm

TOP FEATURES

Integration/control with TechniSat CONNECT

For using with water based room radiators

temperature indicator in the display

LED signaling for interactive operation

Real-Time Control (FLiRS)

Adapters for Danfoss valves

AMBIENT OPERATING CONDITIONS

IP class : 20

Ambient temperature : 0 bis 40 °C

FUNK COMMUNICATION

Telecommunication : Z-Wave Plus

Range inside : max. 40 m

operating frequency : 868.42 MHz

OTHER FEATURES

Battery change indicator : Ja

POWER SUPPLY

Nominal voltage : 3 V

Non rechargeable battery : 2 x 1.5 V AA alkaline, class III

SENSOR

Sensor type : Programmable electronic radiator thermostat

Standard area : 8 - 28 °C

SCOPE OF DELIVERY

Heizkörperthermostat 2, adapter for Danfoss valves, screws for adapter, 2 alkaline AA batteries, operating instructions